

Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (7.5/6.5/20 °C) [W]	Power (7.5/6.5/24 °C) [W]	Power (5.5/4.5/24 °C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
H-608	555	773	65-70	515	50-55	515	0,67	7,9	2,8	348	314	156	300
HX-608	555	773	90-95	50	60-65	515	0,67	8,0	2,8	348	314	156	300
H-610	555	1043	65-70	515	50-55	515	0,97	11,4	3,9	495	446	219	300
HX-610	555	1043	90-95	50	60-65	515	0,97	11,5	3,9	495	446	219	300
H-616	555	1583	65-70	515	50-55	515	1,53	17,7	6,1	763	688	337	600
HX-616	555	1583	90-95	50	60-65	515	1,53	17,8	6,1	763	688	337	600

Horizontal profiles:		Vertical manifolds:	
Finish and guarantee:	- standard: phosphatizing + polyester-epoxy lacquer, 5 year guarantee; - on request: electrophoresis + polyester-epoxy lacquer, 10 year guarantee;		
Mounting brackets:	- set for assembly on the wall - brackets in the colour of a towel rail		
Valve:	for a separate order – page 25		
Heater:	for a separate order – page 24		
Working pressure:	4 bars		
Maximal temperature:	95 °C		
Connections:			- inner threads G 1/2 - air-vent plug G1/8 hidden behind

