



RADIK® ZÁKLADNÍ TECHNICKÉ PARAMETRY

RADIK KLASIK, RADIK VK, RADIK VKU, RADIK VKL

	Typ 10 Typ 10 VK Typ 10 VKL					Typ 11 Typ 11 VK Typ 11 VKL					Typ 20 Typ 20 VK Typ 20 VKL Typ 20 VKU					
Výška H [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900	
Jmenovitý tepelný výkon [W/m]	330	423	514	604	875	549	708	858	1002	1394	554	698	838	978	1398	
Tepelný exponent n [-]	1,3319	1,3193	1,3068	1,2942	1,3083	1,3156	1,3140	1,3123	1,3107	1,3206	1,2986	1,2995	1,3005	1,3014	1,3548	
K_T	c_0		0,01983700			1,29050000			0,01407200		1,34220000		0,05138300		1,28720000	
b	c_1		0,81190000			0,00003492			0,94200000		-0,00004407		0,73450000		0,00005091	
Hmotnost tělesa [kg/m]	6,38	8,40	10,41	12,43	19,20	10,42	14,15	17,87	21,60	32,80	13,00	17,23	21,47	25,70	38,70	
Vodní objem [l/m]	1,9	2,3	2,7	3,1	4,3	1,9	2,3	2,7	3,1	4,3	3,7	4,4	5,1	5,8	8,3	
Průtokový součinitel A_T [m ²]	$6,5 \times 10^{-5}$ (DN 15)					$6,5 \times 10^{-5}$ (DN 15)					$1,0 \times 10^{-4}$ (DN 15)					
Součinitel odporu ξ_T [-]	19,0 (DN 15)					19,0 (DN 15)					8,5 (DN 15)					

Uvedené hodnoty pro průtokový součinitel A_T a součinitel odporu ξ_T platí pouze pro model RADIK KLASIK.

RADIK VKM

	Typ 10 VKM					Typ 11 VKM					Typ 20 VKM					
Výška H [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900	
Jmenovitý tepelný výkon [W/m]	375	476	572	665	922	533	683	831	979	1432	627	784	934	1080	1502	
Tepelný exponent n [-]	1,2945	1,3013	1,3081	1,3149	1,3331	1,2583	1,2772	1,2962	1,3151	1,3291	1,2960	1,3027	1,3093	1,3160	1,3456	
K_T	c_0		0,01616400			1,32460000			0,03737600		1,27140000		0,05474000		1,30360000	
b	c_1		0,85720000			-0,00001748			0,79480000		0,00004924		0,73930000		0,00002583	
Hmotnost tělesa [kg/m]	6,90	8,77	10,63	12,50	18,50	10,29	13,48	16,67	19,86	31,00	13,67	17,58	21,50	25,42	37,50	
Vodní objem [l/m]	1,9	2,3	2,7	3,1	4,5	1,9	2,3	2,7	3,1	4,5	3,7	4,5	5,3	6,2	8,7	

RADIK MM

	Typ 10 MM					Typ 11 MM					Typ 20 MM					
Výška H [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900	
Jmenovitý tepelný výkon [W/m]	359	464	564	661	927	572	728	876	1017	1404	581	735	884	1032	1469	
Tepelný exponent n [-]	1,2848	1,2852	1,2856	1,286	1,3011	1,2631	1,2693	1,2754	1,2816	1,3014	1,2893	1,2982	1,3071	1,3160	1,3321	
K_T	c_0		0,01042300			1,31201000			0,02394200		1,30032000		0,04454500		1,29117000	
b	c_1		0,93910200			-0,00003545			0,88171000		-0,00002999		0,76841900		0,00003559	
Hmotnost tělesa [kg/m]	6,38	8,40	10,41	12,43	19,20	10,42	14,15	17,87	21,60	32,80	13,00	17,23	21,47	25,70	38,70	
Vodní objem [l/m]	1,9	2,3	2,7	3,1	4,3	1,9	2,3	2,7	3,1	4,3	3,7	4,4	5,1	5,8	8,3	
Průtokový součinitel A_T [m ²]	$3,399 \times 10^{-5}$ (DN 15)					$3,399 \times 10^{-5}$ (DN 15)					$3,906 \times 10^{-5}$ (DN 15)					
Součinitel odporu ξ_T [-]	70 (DN 15)					70 (DN 15)					53 (DN 15)					



RADIK® ZÁKLADNÍ TECHNICKÉ PARAMETRY

RADIK KLASIK, RADIK VK, RADIK VKU, RADIK VKL

	Typ 21 Typ 21 VK Typ 21 VKL Typ 21 VKU					Typ 22 Typ 22 VK Typ 22 VKL Typ 22 VKU					Typ 33 Typ 33 VK Typ 33 VKL Typ 33 VKU						
Výška H [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900		
Jmenovitý tepelný výkon [W/m]	745	937	1117	1288	1754	966	1216	1452	1679	2313	1379	1738	2079	2406	3328		
Teplotní exponent n [-]	1,3197	1,3238	1,3278	1,3319	1,3578	1,3297	1,3316	1,3334	1,3353	1,3574	1,2977	1,3129	1,3282	1,3434	1,3626		
K_T	c_0		0,033993000			1,35050000			0,05120200			1,34380000			0,07428700		1,33630000
b	c_1		0,83090000			-0,00002395			0,80550000			-0,00000514			0,80730000		-0,00000262
Hmotnost tělesa [kg/m]	15,60	20,57	25,53	30,50	47,00	18,40	24,37	30,33	36,30	56,30	27,70	36,83	45,97	55,10	84,50		
Vodní objem [l/m]	3,7	4,4	5,1	5,8	8,3	3,7	4,4	5,1	5,8	8,4	5,3	6,4	7,6	8,7	12,6		
Průtokový součinitel A_T [m ²]	1,0 x 10 ⁻⁴ (DN 15)					1,0 x 10 ⁻⁴ (DN 15)					1,18 x 10 ⁻⁴ (DN 15)						
Součinitel odporu ξ_T [-]	8,5 (DN 15)					8,5 (DN 15)					5,8 (DN 15)						

Uvedené hodnoty pro průtokový součinitel A_T a součinitel odporu ξ_T platí pouze pro model RADIK KLASIK.

RADIK VKM

	Typ 21 VKM					Typ 22 VKM					Typ 33 VKM						
Výška H [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900		
Jmenovitý tepelný výkon [W/m]	748	937	1118	1294	1802	950	1204	1447	1680	2335	1331	1716	2075	2411	3286		
Teplotní exponent n [-]	1,3135	1,3259	1,3384	1,3508	1,3791	1,2985	1,3122	1,3260	1,3397	1,3609	1,3190	1,3273	1,3357	1,3440	1,3708		
K_T	c_0		0,05250800			1,33530000			0,04268400			1,33820000			0,02273700		1,39030000
b	c_1		0,75670000			0,00002048			0,83910000			-0,00000944			0,98690000		-0,00007695
Hmotnost tělesa [kg/m]	15,50	20,22	24,94	29,67	45,17	17,90	23,60	29,30	35,00	54,00	26,20	34,70	43,20	51,70	80,75		
Vodní objem [l/m]	3,7	4,5	5,3	6,2	8,7	3,7	4,5	5,3	6,2	8,9	5,4	6,7	8,0	9,3	13,0		

RADIK MM

	Typ 21 MM					Typ 22 MM					Typ 33 MM						
Výška H [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900		
Jmenovitý tepelný výkon [W/m]	736	932	1114	1284	1731	982	1233	1472	1702	2357	1279	1665	2028	2369	3258		
Teplotní exponent n [-]	1,2990	1,3075	1,3161	1,3246	1,3517	1,2941	1,3069	1,3197	1,3325	1,3408	1,3036	1,3122	1,3208	1,3294	1,3487		
K_T	c_0		0,02336240			1,35811000			0,06657990			1,31712000			0,01766570		1,37772000
b	c_1		0,89572800			-0,00005488			0,77778600			0,00000880			1,03453000		-0,00008574
Hmotnost tělesa [kg/m]	15,60	20,57	25,53	30,50	47,00	18,40	24,37	30,33	36,30	56,30	27,70	36,83	45,97	55,10	84,50		
Vodní objem [l/m]	3,7	4,4	5,1	5,8	8,3	3,7	4,4	5,1	5,8	8,4	5,3	6,4	7,6	8,7	12,6		
Průtokový součinitel A_T [m ²]	3,906 x 10 ⁻⁵ (DN 15)					3,906 x 10 ⁻⁵ (DN 15)					3,906 x 10 ⁻⁵ (DN 15)						
Součinitel odporu ξ_T [-]	53 (DN 15)					53 (DN 15)					53 (DN 15)						