



Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20 °C) [W]	Power (75/65/24 °C) [W]	Power (65/45/24 °C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
B-609	550	904	65-70	50	50-55	510	0,51	6,1	3,1	301	271	132	-
B-611	550	1120	65-70	50	50-55	510	0,61	7,3	3,7	362	326	158	-
B-613	550	1336	65-70	50	50-55	510	0,72	8,5	4,2	424	381	184	-



Circuit profile:



Finish and guarantee:

- standard: phosphatizing + polyester-epoxy lacquer;
5 year guarantee;
- on request: electrophoresis + polyester-epoxy lacquer;
10 year guarantee;

Mounting brackets:

- set for assembly on the wall
- brackets in the colour of a towel rail

Valve:

for a separate order – page 25

Heater:

for a separate order – page 24


Working pressure:

4 bars

Maximal temperature:

95 °C

Connections:



- inner threads G 1/2
- air-vent plug G1/8
hidden behind

