



Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m <sup>2</sup> ]	Weight [kg]	Capacity [dm <sup>3</sup> ]	Power (7.5/65/20 °C) [W]	Power (7.5/65/24 °C) [W]	Power (5.5/45/24 °C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
B-609	550	904	65-70	50	50-55	510	0,51	6,1	3,1	301	271	132	-
B-611	550	1120	65-70	50	50-55	510	0,61	7,3	3,7	362	326	158	-
B-613	550	1336	65-70	50	50-55	510	0,72	8,5	4,2	424	381	184	-



Circular profile:



Finish and guarantee:	<ul style="list-style-type: none"> <li>- standard: phosphatizing + polyester-epoxy lacquer; 5 year guarantee;</li> <li>- on request: electrophoresis + polyester-epoxy lacquer; 10 year guarantee;</li> </ul>
Mounting brackets:	<ul style="list-style-type: none"> <li>- set for assembly on the wall</li> <li>- brackets in the colour of a towel rail</li> </ul>
Valve:	for a separate order – page 25
Heater:	for a separate order – page 24
Working pressure:	4 bars
Maximal temperature:	95 °C
Connections:	<ul style="list-style-type: none"> <li>- inner threads G 1/2</li> <li>- air-vent plug G1/8 hidden behind</li> </ul>

