


Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20 °C) [W]	Power (75/65/24 °C) [W]	Power (55/45/24 °C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
DCh-408	450	776	92-112	400	45-65	250	0,61	6,5	3,2	209	188	92	-
DCh-412	450	1154	92-112	400	45-65	250	0,91	9,5	4,8	308	277	134	300
DCh-417	450	1742	92-112	400	45-65	250	1,39	14,3	7,4	470	422	202	300
DCh-608	600	776	104-124	550	45-65	400	0,78	8,0	4,0	270	243	119	-
DCh-612	600	1154	104-124	550	45-65	400	1,16	11,7	5,9	398	358	174	300
DCh-617	600	1742	104-124	550	45-65	400	1,77	17,8	9,1	609	547	262	600



Finish and guarantee:	galvanic chrome – 5 year guarantee
Mounting brackets:	set for assembly on the wall; brackets in the colour of a towel rail
Valve:	for a separate order – page 25
Heater:	for a separate order – page 24
Accessories:	for a separate order – page 26
Working pressure:	10 bars
Maximal temperature:	95 °C
Connections:	– inner threads G 1/2 – air-vent plug G1/8 hidden behind

