Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m²]	Weight [kg]	Capacity [dm³]	Power (75/65/20°C) [W]	Power (75/65/24°C) [W]	Power (55/45/24°C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
F-509	502	818	97-102	406	52-57	440	0,68	8,3	4,0	410	369	180	300
FX-509	502	818	97-102	50	86-91	440	0,68	8,4	4,0	410	369	180	300
F-513	502	1238	97-102	406	52-57	440	1,06	12,7	6,2	631	568	276	600
FX-513	502	1238	97-102	50	86-91	440	1,06	12,8	6,2	631	568	276	600
F-517	502	1742	97-102	406	52-57	440	1,53	18,1	8,9	905	813	392	900
FX-517	502	1742	97-102	50	86-91	440	1,53	18,2	8,9	905	813	392	900
F-609	595	818	106-111	500	52-57	525	0,79	9,3	4,5	470	423	207	300
FX-609	595	818	106-111	50	95-100	525	0,79	9,4	4,5	470	423	207	300
F-613	595	1238	106-111	500	52-57	525	1,23	14,3	6,9	726	654	320	600
FX-613	595	1238	106-111	50	95-100	525	1,23	14,4	6,9	726	654	320	600
F-617	595	1742	106-111	500	52-57	525	1,77	20,3	10,0	1032	928	450	900
FX-617	595	1742	106-111	50	95-100	525	1,77	20,4	10,0	1032	928	450	900
F-809	746	818	120-125	650	52-57	679	0,94	10,7	5,1	561	505	245	300
FX-809	746	818	120-125	50	109-114	679	0,94	10,8	5,1	561	505	245	300
F-813	746	1238	120-125	650	52-57	679	1,48	16,5	8,0	866	778	375	600
FX-813	746	1238	120-125	50	109-114	679	1,48	16,6	8,0	866	778	375	600
F-817	746	1742	120-125	650	52-57	679	2,13	23,6	11,5	1250	1123	538	900
FX-817	746	1742	120-125	50	109-114	679	2,13	23,6	11,5	1250	1123	538	900

Horizontal tubes:

Vertical manifolds: 

Finish and guarantee:	– standard: phosphatizing + polyester-epoxy lacquer; 5 year guarantee; – on request: electrophoresis + polyester-epoxy lacquer; 10 year guarantee;
Mounting brackets:	– set for assembly on the wall – brackets in the colour of a towel rail
Valve:	for a separate order – page 25
Heater :	for a separate order – page 24
Accessories:	for a separate order – page 26
Working pressure:	4 bars
Maximal temperature:	95 °C
Connections:	F: 1/2 – 1/8; FX: 1/2 – MM – 1/8 – inner threads G 1/2; – air-vent plug G1/8 hidden behind

FX



F