


Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connection's distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20+°C) [W]	Power (75/65/24+°C) [W]	Power (55/45/24+°C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
FCh-509	502	818	97-117	406	52-72	300	0,68	8,5	4,0	238	214	104	-
FCh-513	502	1238	97-117	406	52-72	300	1,06	12,9	6,2	366	329	160	300
FCh-517	502	1742	97-117	406	52-72	300	1,53	18,2	8,9	525	472	228	300
FCh-609	595	818	106-126	500	52-72	400	0,79	9,4	4,5	273	246	120	-
FCh-613	595	1238	106-126	500	52-72	400	1,23	14,4	6,9	421	379	186	300
FCh-617	595	1742	106-126	500	52-72	400	1,77	20,4	10,0	599	539	261	600

Horizontal tubes:



Vertical manifolds:



Finish and guarantee:	galvanic chrome - 5 year guarantee	
Mounting brackets:	- set for assembly on the wall - brackets in the colour of a towel rail	
Valve:	for a separate order - page 25	
Heater :	for a separate order - page 24	
Accessories:	for a separate order - page 26	
Working pressure:	4 bars	
Maximal temperature:	95 °C	
Connections:		- inner threads G 1/2 - air-vent plug G1/8 hidden behind

