


Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connection distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power 75.65/20 °C [W]	Power 75.65/24 °C [W]	Power 55.45/24 °C [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
FXB-608	595	776	106-111	50	53-58	525	0,74	10,1	4,2	440	397	194	300
FXB-612	595	1154	106-111	50	53-58	525	1,14	14,6	6,4	669	602	295	600
FXB-617	595	1742	106-111	50	53-58	525	1,77	21,7	10,0	1031	927	450	900
FXB-808	746	776	120-125	50	53-58	679	0,87	11,4	4,8	519	467	227	300
FXB-812	746	1154	120-125	50	53-58	679	1,35	16,5	7,4	791	711	342	600
FXB-817	746	1742	120-125	50	53-58	679	2,12	24,8	11,5	1243	1116	535	900



Horizontal tubes:



Vertical manifolds:

Finish and guarantee:

- standard: phosphatizing + polyester-epoxy lacquer; 5 year guarantee;
- on request: electrophoresis + polyester-epoxy lacquer; 10 year guarantee;

Mounting brackets:

- set for assembly on the wall
- brackets in the colour of a towel rail

Valve:

- integrated, hidden under cover
- thermostatic valve included

Heater:

for a separate order - page 24

Accessories:

for a separate order - page 26

Working pressure:

4 bars

Maximal temperature:

95 °C

Connections:



- inner threads G 1/2
- air-vent plug G1/8 hidden behind

Remarks:

- water inlet at the left side
- thermostatic head in chrome

